

Trend Analysis of the Brazilian Scientific Production in Computer Science

Caio Cesar Trucolo, Student at the Masters Program in Information Systems, USP, Luciano Antonio Digiampietri, Ph.D. Prof. at the undergraduate and graduate programs in Information Systems at USP

Abstract—The growth of scientific information volume and diversity brings new challenges in order to understand the reasons, the process and the real essence that propel this growth. This information can be used as the basis for the development of strategies and public politics to improve the education and innovation services. Trend analysis is one of the steps in this way. In this work, trend analysis of Brazilian scientific production of graduate programs in the computer science area is made to identify the main subjects being studied by these programs in general and individual ways.

Keywords—Trend Analysis, Academic Social Networks, Computer Science

I. Introduction

In order to understand the behavior of individuals or of a group of individuals that belong to a social circle and create any kind of knowledge, such as opinions in Internet portals or papers in scientific journals, we need more than one single type of analysis.

The change of the behavior with time can be considered as one of the topics to be analyzed. Since the behavior of groups and individuals changes with time, several services try to identify or forecast trends in order to increase business competitiveness or to establish adequate policies for those variations.

The analysis of the behavior of the Brazilian scientific production may be considered a challenge due to the fact that Brazil is the fifth largest country in the world, has the fifth largest population and a huge cultural diversity. In the last decades, the number of Brazilian papers increased exponentially (close to 12% per year), growing from little more than 10,000 full papers published in 1980 to almost 400,000 in 2010, according to data obtained from the analysis of more than one million Lattes curricula [1].

The understanding of the characteristics of this production allows the creation of public strategies and policies that go together with the scientific trends, increasing even more the Brazilian potential in this context.

This paper aims to analyze part of the Brazilian scientific production, most specifically, the one in the area of computer science. The goal of this work is to develop and apply a methodology to identify trends in subjects and

Corresponding author: Luciano Digiampietri, digiampietri@usp.br

research branches in the *stricto sensu* graduate programs evaluated by CAPES, based on the information included in the curricula of the advisor professors that are stored in the Lattes platform. Besides, we performed a network analysis of co-authorship in order to verify if there are strong relations between the verified trends and the co-authorship networks. It is important to point out that this paper intends to verify current trends based on a historical analysis. It is out of its scope to verify the diffusion and popularization speed of these trends within the programs. This analysis helps identifying the directions taken by research in Computer Science in Brazil, which may help researchers identify growing fields and helping the process of evaluating new research projects.

The rest of this paper is organized as follows. Section 2 summarizes related work, section 3 presents the Lattes platform and its importance as a guideline for the national scientific production. Methodology is described in section 4, section 5 presents and analyzes the results and, at last, section 6 presents the final considerations.

II. Related work

POR the last years, several papers analyzed trends for different types of applications, which span from social networks to stock markets. Among those works the ones closer to this are those that study historical text documents.

In the work of Bolelli et al. [2], Lattent Dirichilet Allocation and Gibbs Sampling were used together with the time order of the documents to create a generative model that learn author, topic and word distributions. In a synthetic application, the accuracy was approximately 72%.

The work of Kawamae [3] consisted of trying to forecast the topic distribution in scientific articles taking the time distribution into consideration. Based on the same idea, a new work [4] established the difference between stable topics (that do not have a significant variation with time) and dynamics ones, trying to refute other models that only take into consideration the topic explosion (sudden increases of topic presence during some periods of time). For the evaluation, the author compared the proposed model with two others using the perplexity and the L1 error rate. At last, the model presents those two rates

smaller than the other two models, achieving an average L1 of 2.44.

Jayashri and Chitra [5] proposed a model with an ART network (*Adaptive Resonance Theory*) to identify topics in scientific documents from different databases and to detect trends using the peaks of those extracted topics. The approach used was able to detect the topics in vogue for different databases.

Park et al. [6] used a trend detection approach using characteristic selection based on IG-I (*Improved Gini - Index*). For each topic given as input, subtopics were extracted to analyze its time behavior and identify it as growing or decreasing. For the four topics given as input to the model, F1 measurement tests were perform together with SVM (*Support Vector Machine*) and kNN (*k - nearest neighbors*). The F1 result for SVM was 0.982 and for kNN was 0.916. One limitation of this method is that the process is not fully automatic.

Abe e Tsumoto [7] selected important terms using TF-IDF (Term Frequency - Inverse Document Frequency) and the Jaccard coefficient using linear regression a posteriori to detect emerging trends. All the detected trends were confirmed as real ones by domain experts.

Besides the textual documents used as basis for trend analysis, in the last years social networks have also been used to help this analysis. The work of Cimenler, Reeves and Skvoretz [8] analysis using mostly centrality metrics in order to understand how significant these metrics are to forecast the performance of researchers using citation indices such as the h-index. The Poisson regression method is used to analyze the importance of the metrics for some types of networks formed by researchers from an Engineering college.

A systematic review on trend identification and analysis techniques for other applications besides historic text documents can be found in [9].

This work deepens the application in an interesting way. The data extracted from the Lattes platform allow for a fairly rich analysis on the national scientific condition. We can say, therefore, that this work differs from the previous works from the good approximation of the analysis to the national scientific reality. Another important characteristic is the fact that this analysis does not require human effort, that is, the trend analysis is perform based on terms and expressions automatically extracted from the database without the need to manually establish the importance of terms or limit values to the trends.

III. LATTES PLATFORM

THE Lattes platform is a Brazilian database that stores curricula from researchers and whose rule is of the utmost importance to academia. There are more than three million curricula stored with important information to the analysis of researchers and academic networks. In this platform it is possible to obtain data from researchers such as scholar information, area of work, bibliographic production, participation in thesis committees, advisor work and much more.

For this work, we selected 57.501 different papers, without the repetitions and redundancies caused by the characteristics of the platform. This number is distributed among the 45 Brazilian graduate programs on Computer Science and contains published papers from 1991 up to 2011. We decided to use the papers up to 2011 because we verified that the number of papers in general falls dramatically after 2011 because, in average, the users take more than a year to update their curricula [1]. Due to the fact that there was no dramatic change in national scientific policies in the last years, we assume that using data up to 2011 we can identify trends in a sufficiently precise and current way.

IV. METHODOLOGY

HE entire analysis process was performed in three steps: data gathering, automatic term extraction and trend analysis of the extracted terms.

A. Data gathering

N order to gather the data, we first identified the advisors of the 45 stricto sensu graduate programs in computer science¹. The information of the researchers curricula were tabulated and stored into a database according to the methodology described in [10]. In order to perform the tests, we extract the terms from 57,501 publication titles distributed from the 45 programs and published from 1991 up to 2011. These terms were then submitted to trend analysis considering publications from a single program and, afterwards, from all the graduate programs.

B. Automatic term extraction

HE automatic term extraction technique used consists in determining the most important terms in the set of document by the adjacent frequency of the words that compose these terms. The formula used to calculate the weights for each candidate term is the following:

$$FED\left(TC\right) = f\left(TC\right) \times \left(\prod_{i=1}^{T} \left(FE\left(N_{i}\right) + 1\right) \times \left(FD\left(N_{i}\right) + 1\right)\right)^{1 \div T} > 1$$

where f(TC) is the frequency of the candidate term, TC, and FE(Ni) and FD(Ni) indicate the frequency of the candidates to the left and to the right, respectively. This formula is described in details in [11].

A list of *stop words* in Portuguese, Spanish and English was used to filter the candidate terms.

We observed empirically that the composite terms were more meaningful than the simple terms in relation to the subject matters approached by the publications. Hence, the terms used in the trend analysis phase were the composite terms and the ones with higher weights.

¹This information was obtained from the triennium report referring to the period 2007-2009.

C. Trend Analysis

Based on the extracted terms, we calculated the importance indices of the terms for each period (year). The importance index used in this paper is the TF-IDF (Term Frequency divided by Inverse Document Frequency), which is one of the most used indices to infer the importance of terms. With the calculated indices, we performed linear and non-linear regression in order to determine the trend curves that most fit the time series for each term. The regression types used were linear, exponential, logarithmic, power law and polynomial, with degrees from two to five. Afterwards, we calculated the quadratic error for each trend curve generated in order to determine the curve that best fits the time series for each term.

The classification of terms as trends was based on the forecasting, based on the best fit trend curve (that is, the one with the smallest quadratic error), for the first year after the historical analysis interval: the year of 2011. In spite of the fact that trend analysis approach used allows for forecasting of posterior years, we decided to use only the year after the historical analysis because this index already indicates the trend pointed out by the regression curve.

V. Results

FIGURE 1 presents the time behavior of three terms extracted based on the TF-IDF indices which were calculated with the trend analysis techniques. It is possible to see the big difference between the behaviors of these three terms. While the term sensor networks had a huge increase in the last few years, object oriented decreased significantly. Meanwhile, the term neural networks has been used in research for a while, and its time series has some ups and downs in the period under analysis, but has shown a quite stable behavior.




Fig. 1. Time behavior of three terms

Figures 2 and 3 show the trend curves based on nonlinear 3-degree polynomial regression and power law, respectively, of the terms sensor networks and object oriented. We can see in figure 2 that the term sensor networks growth started at the year 2000 while the term object oriented was increasing between the years 1998 and 2000, when it started to decrease. Comparing both behaviors, it becomes clear in this context that the term sensor

networks can be identified as a trend in current research while object oriented cannot.




Fig. 2. Trend curve generated by nonlinear $power\; law$ regression for the term $sensor\; networks$




Fig. 3. Trend curve generated by nonlinear 3-degree polynomial regression for the term $object\ oriented$

In a global analysis, the table I shows the 20 term with the highest TF-IDF in the forecast for 2011, that is, the terms with the highest popularity trends. Comparing the forecast values with the real values for 2011, we observed an error of approximately 26.5% and a high correlation between the forecast values and the real ones (about 0.68).

Besides a global analysis, we identified the individual trends for each program. Based on that information, it is possible to see some characteristics of the research works for each program and whether they follow a national trend. Table II presents the main trends for one of the analyzed programs. It is clear that this program is highly interested in topics related to artificial intelligence, with a focus on the image retrieval application.

For a global view of the Brazilian graduate programs in Computer Science, table III shows the main trends for each one of the 45 programs evaluated by CAPES.

At last, we performed an analysis of co-authorship networks among professors in these graduate programs in order to verify if the trends we found are strongly correlated to the co-authorship networks.

Figure 4 contains the co-authorship network for full papers published by the professors of the 45 programs under analysis. The numbers presented in the caption

| Term | Forecast TF-IDF for 2011 |
|-----------------------------|--------------------------|
| product line | 413.57 |
| wireless sensor | 402.99 |
| sensor networks | 321.47 |
| wireless sensor networks | 320.69 |
| neural networks | 277.29 |
| software product | 255.62 |
| product lines | 243.05 |
| software development | 238.76 |
| particle swarm optimization | 227.22 |
| swarm optimization | 227.22 |
| particle swarm | 224.63 |
| optimum-path forest | 219.73 |
| augmented reality | 209.51 |
| time series | 208.92 |
| genetic algorithm | 207.47 |
| case study | 204.01 |
| scheduling problem | 181.71 |
| social networks | 181.41 |
| infocomp ufla | 176.29 |
| genetic programming | 173.48 |

TABLE II
EXAMPLE OF TRENDS IN ONE OF THE PROGRAMS

| Term | Forecast TF-IDF for 2011 |
|----------------------------|--------------------------|
| neural networks | 63.36 |
| time series | 56.65 |
| artificial neural | 51.89 |
| artificial neural networks | 51.84 |
| product lines | 30.05 |
| image retrieval | 24.86 |
| access methods | 24.33 |
| feature selection | 21.57 |

correspond to the same numbers used in tables III and IV. Each node in this network corresponds to a professor and each edge indicates co-authorship between the two professors connected by it. It is possible to observe in the graph the existence of a big connected component in the center of the image and the prevalence of colored edges (which indicate co-authorship between professors from the same graduate program). On the other hand, edges in gray represent collaborations between professors from different programs².

Table 4 presents for each graduate program the two programs most related to it, using the number of co-authorship relationships as metric. It is possible to realize that when crossing the information on tables 3 and 4 that the co-authorship relationship between programs is not very much related to the research tendencies in each pair of programs. Taking into consideration the information in tables 3 and 4, that is, the main research terms for each program and the two programs most related to each one, less than 9% have equal terms. One of these cases is, for instance, the case for programs 6 (UNICAMP - Computer Science) and 40 (UNESP/SJRP - Computer Science), which are programs that have some co-authorship relationships and share the term optimum-path forest which, as

verified manually, is part of the title of papers published in co-authorship between professors in both programs. This can be an indication that the trends developed in each program usually are a result from internal collaborations, while the collaborations between programs are related to wider works (potentially in consolidated subjects). We intend to study this hypothesis deeper in future works. A more specific discussion on productivity and co-authorship between Brazilian graduate programs in Computer Science can be found in [12], [13].

VI. Final Considerations

THIS work presented general information on the trends in the Brazilian scientific production in the Computer Science field using an automatic term and expression identification technique. We performed an analysis of the general trends and individual analysis for each program. Thus, it was possible to identify which subjects are in vogue and which are disregarded. Besides, we perform an analysis of the co-authorship networks of the advisor professors in the graduate programs in the field of Computer Science in which we observed that there is no strong correlation between the trends we found in each program and the co-authorship between them.

The results found in this paper are an initial step if we consider the full potential of the trend analysis of the national scientific production. In future works, the structure of the sources of information will be included as a factor for analysis. This way, the academic social networks will be treated as a new variable to increase the accuracy of the new trend forecasting model.

Besides, we intend to group professors and terms according to the subareas of Computer Science in order to identify the dynamics and the publication trends in those subareas.

²A figure containing only the information from the 13 programs with the best evaluations from CAPES can be found in: http://www.each.usp.br/digiampietri/FSMA/maioresprogramas.png




Fig. 4. Co-authorship networks from the analyzed programs

| | Programa | Primeira tendência | Segunda tendência |
|-----|---|---|---|
| 1 | PUC-RIO - INFORMATICS | product line | microscopy images |
| 2 | UFMG - COMPUTER SCIENCE | genetic programming | name disambiguation |
| 3 | UFRJ - COMPUTER AND SYSTEMS ENGINEERING | hyperbolic smoothing | clustering method |
| 4 | UFPE - COMPUTER SCIENCE | software development | time series |
| 5 | UFRGS - COMPUTING | sensor networks | eye fundus images |
| 6 | UNICAMP - COMPUTER SCIENCE | optimum-path forest | foresting transform |
| 7 | USP / SC - COMPUTER SCIENCE AND | neural networks | time series |
| | COMPUTATIONAL MATHEMATICS | | |
| 8 | UFF - COMPUTING | wave propagation | cellular automata |
| 9 | USP - COMPUTER SCIENCE | oriented relational | field-research oriented relational database |
| 10 | PUC / PR - INFORMATICS | arq scheme | music genre |
| 11 | PUC / RS - COMPUTER SCIENCE | promising protein receptor snapshots | infocomp (ufla |
| 12 | UFAM - INFORMATICS | grounded theory | medical devices |
| 13 | UFBA - COMPUTER SCIENCE - UFBA - UNIFACS | real-time systems | failure detectors |
| 14 | UFC - COMPUTER SCIENCE | software product | data integration |
| 15 | UFCG - COMPUTER SCIENCE | power management | application user interfaces |
| 16 | UFES - INFORMATICS | fault diagnosis | matrices reordering algorithms |
| 17 | UFMS - COMPUTER SCIENCE | shuffling experiments | e-sapi bovis |
| 18 | UFPR - INFORMATICS | swarm optimization | particle swarm optimization |
| 19 | UFRJ - INFORMATICS | three protagonist businessmen | visual impairment |
| 20 | UFRN - SISTEMAS E COMPUTAÇÃO | product line | wireless sensor |
| 21 | UFSC - COMPUTER SCIENCE | image segmentation | cronic non-transmissible |
| 22 | UFSCAR - COMPUTER SCIENCE | production scheduling | engenharia elétrica |
| 23 | UFU - COMPUTER SCIENCE | trace alignment | diferenciais parciais |
| 24 | UNB - INFORMATICS | particle swarm optimization | particle swarm |
| 25 | UNIFOR - APPLIED INFORMATICS | wireless sensor | decision analysis |
| 26 | UNISINOS - APPLIED COMPUTING | multilevel approach | composite structure |
| 27 | FESP / UPE - COMPUTER ENGINEERING | time series | particle swarm optimization |
| 28 | IME - SYSTEMS AND COMPUTING | upper bound | web services |
| 29 | PUC / MG - INFORMATICS | sensor networks | graph matching |
| 30 | UCPÉL - INFORMATICS | simulação quântica | architecture using |
| 31 | UECE - COMPUTER SCIENCE | test case | release planning |
| 32 | UEL - COMPUTER SCIENCE | spectral analysis | detection using |
| 33 | UEM - COMPUTER SCIENCE | users personomy | personomy using |
| 34 | UERN - COMPUTER SCIENCE - UERN - UFERSA | sensor networks | transcoded videos |
| 35 | UFG - COMPUTER SCIENCE | capacitated arc | capacitated arc routing |
| 36 | UFPA - COMPUTER SCIENCE | iso/iec 12207 | neurais artificiais |
| 37 | UFPB / J.P INFORMATICS | naive bayes | training assessment |
| 38 | UFSM - INFORMATICS | cognitive style | adaptive hypermedia |
| 39 | UFV - COMPUTER SCIENCE | scheduling problem | sequence dependent setup |
| 40 | UNESP / SJRP - COMPUTER SCIENCE | optimum-path forest | contours initialized |
| 41 | UNIFACS - SYSTEMS AND COMPUTING | developers context-specific preferred representational | preferred representational |
| 42 | UNIFEI - COMPUTER SCIENCE AND TECHNOLOGY | rough sets | self-organizing map model |
| 43 | UNIMEP - COMPUTER SCIENCE | realidade aumentada | augmented reality |
| 44 | UNIRIO - INFORMATICS | business models | case study |
| 45 | UNIVALI - COMPUTING | process capability models | neurais artificiais |
| -10 | on one of the | process capability models | mourant di tilicidio |

REFERENCES

TABLE IV Most related programs in terms of co-authorship

| | Program | Most related program | Second most related program |
|----|--|---|---|
| 1 | PUC-RIO - INFORMATICS | UNIRIO - INFORMATICS | UFF - COMPUTING |
| 2 | UFMG - COMPUTER SCIENCE | UFAM - INFORMATICS | PUC / MG - INFORMATICS |
| 3 | UFRJ - COMPUTER AND SYSTEMS ENGINEERING | UFRJ - INFORMATICS | UFF - COMPUTAÇÃO |
| 4 | UFPE - COMPUTER SCIENCE | FESP / UPE - COMPUTER ENGINEERING O | USP / SC - COMPUTER SCIENCE AND COMPUTATIONAL MATHEMATICS |
| 5 | UFRGS - COMPUTAÇÃO | PUC / RS - COMPUTER SCIENCE | UCPEL - INFORMATICS |
| 6 | UNICAMP - COMPUTER SCIENCE USP / SC - COMPUTER SCIENCE AND | UNESP / SJRP - COMPUTER SCIENCE | UFMG - COMPUTER SCIENCE |
| 7 | COMPUTATIONAL MATHEMATICS | UFRN - SYSTEMS AND COMPUTING | UFSCAR - COMPUTER SCIENCE |
| 8 | UFF - COMPUTING | UFRJ - COMPUTER AND SYSTEMS ENGINEERING | PUC-RIO - INFORMATICS |
| 9 | USP - COMPUTER SCIENCE | UFMS - COMPUTER SCIENCE | FESP / UPE - COMPUTER ENGINEERING |
| 10 | PUC / PR - INFORMATICS | UFPR - INFORMATICS | UFSC - COMPUTER SCIENCE |
| 11 | PUC / RS - COMPUTER SCIENCE | UFRGS - COMPUTING | UCPEL - INFORMATICS |
| 12 | UFAM - INFORMATICS | UFMG - COMPUTER SCIENCE | PUC-RIO - INFORMATICS |
| 13 | UFBA - COMPUTER SCIENCE - UFBA - UNIFACS | USP - COMPUTER SCIENCE | UNIFACS - SYSTEMS AND COMPUTING |
| 14 | UFC - COMPUTER SCIENCE | PUC-RIO - INFORMATICS | UFRJ - COMPUTER AND SYSTEMS ENGINEERING |
| 15 | UFCG - COMPUTER SCIENCE | UFPB / J.P INFORMATICS | UFPE - COMPUTER SCIENCE |
| 16 | UFES - INFORMATICS | UNIRIO - INFORMATICS | PUC-RIO - INFORMATICS |
| 17 | UFMS - COMPUTER SCIENCE | USP - COMPUTER SCIENCE | PUC-RIO - INFORMATICS |
| 18 | UFPR - INFORMATICS | PUC / PR - INFORMATICS | UFMG - COMPUTER SCIENCE |
| 19 | UFRJ - INFORMATICS | UFRJ - COMPUTER AND SYSTEMS | UFRN - SYSTEMS AND COMPUTING |
| 20 | UFRN - SISTEMAS E COMPUTING | ENGINEERING USP / SC - COMPUTER SCIENCE AND COMPUTATIONAL MATHEMATICS | UFRJ - INFORMATICS |
| 21 | UFSC - COMPUTER SCIENCE | UNIVALI - COMPUTING | UFRGS - COMPUTING |
| 22 | UFSCAR - COMPUTER SCIENCE | USP / SC - COMPUTER SCIENCE AND COMPUTATIONAL MATHEMATICS | UFMG - COMPUTER SCIENCE |
| 23 | UFU - COMPUTER SCIENCE | USP / SC - COMPUTER SCIENCE AND COMPUTATIONAL MATHEMATICS | |
| 24 | UNB - INFORMATICS | UFMS - COMPUTER SCIENCE | |
| 25 | UNIFOR - INFORMATICS APLICADA | PUC-RIO - INFORMATICS | UFPR - INFORMATICS |
| 26 | UNISINOS - COMPUTING APLICADA | UFRGS - COMPUTING | PUC / RS - COMPUTER SCIENCE |
| | FESP / UPE - COMPUTER | | , |
| 27 | ENGINEERING | UFPE - COMPUTER SCIENCE | USP - COMPUTER SCIENCE |
| 28 | IME - SYSTEMS AND COMPUTING | PUC-RIO - INFORMATICS | |
| 29 | PUC / MG - INFORMATICS | UFMG - COMPUTER SCIENCE | UFAM - INFORMATICS |
| 30 | UCPEL - INFORMATICS | UFRGS - COMPUTING | PUC / RS - COMPUTER SCIENCE |
| 31 | UECE - COMPUTER SCIENCE | UFF - COMPUTING | UFC - COMPUTER SCIENCE |
| 32 | UEL - COMPUTER SCIENCE | UFRGS - COMPUTING | |
| 33 | UEM - COMPUTER SCIENCE | UNICAMP - COMPUTER SCIENCE | USP / SC - COMPUTER SCIENCE AND COMPUTATIONAL MATHEMATICS |
| 34 | UERN - COMPUTER SCIENCE - UERN - UFERSA | UFRN - SYSTEMS AND COMPUTING | FESP / UPE - COMPUTER ENGINEERING |
| 35 | UFG - COMPUTER SCIENCE | USP - COMPUTER SCIENCE | UFMG - COMPUTER SCIENCE |
| 36 | UFPA - COMPUTER SCIENCE | UFPE - COMPUTER SCIENCE | |
| 37 | UFPB / J.P INFORMATICS | UFCG - COMPUTER SCIENCE | PUC-RIO - INFORMATICS |
| 38 | UFSM - INFORMATICS | PUC / RS - COMPUTER SCIENCE | UCPEL - INFORMATICS |
| 39 | UFV - COMPUTER SCIENCE | | |
| 40 | UNESP / SJRP - COMPUTER SCIENCE | UNICAMP - COMPUTER SCIENCE | |
| 41 | UNIFACS - SYSTEMS AND COMPUTING UNIFEI - COMPUTER SCIENCE AND | PUC-RIO - INFORMATICS | UNICAMP - COMPUTER SCIENCE |
| 42 | TECHNOLOGY | TIEGGAD, GOMPHIED GOLDVOD | |
| 43 | UNIMEP - COMPUTER SCIENCE | UFSCAR - COMPUTER SCIENCE | UFRJ - COMPUTER AND SYSTEMS |
| 44 | UNIRIO - INFORMATICS | PUC-RIO - INFORMATICS | ENGINEERING |
| 45 | UNIVALI - COMPUTING | UFSC - COMPUTER SCIENCE | |

References

- [1] L. Digiampietri, J. Mena-Chalco, J. de Jésus Pérez-Alcázar, E. F. Tuesta, K. Delgado, and R. Mugnaini, "Minerando e caracterizando dados de currículos Lattes," in *Brazilian Workshop on Social Network Analysis and Mining (BraSNAM)*, 2012.
- [2] L. Bolelli, S. Ertekin, D. Zhou, and C. L. Giles, "Finding topic trends in digital libraries," in Proceedings of the 2009 joint international conference on Digital libraries - JCDL '09, New York, New York, USA: ACM Press, Jun. 2009, p. 69, ISBN:
- 9781605583228. DOI: 10.1145/1555400.1555411. [Online]. Available: http://dl.acm.org/citation.cfm? id=1555400.1555411.
- [3] N. Kawamae and R. Higashinaka, "Trend detection model," in *Proceedings of the 19th international conference on World wide web WWW '10*, New York, New York, USA: ACM Press, Apr. 2010, p. 1129, ISBN: 9781605587998. DOI: 10 . 1145 / 1772690 . 1772838. [Online]. Available: http://dl.acm.org/citation.cfm?id=1772690.1772838.
- [4] N. Kawamae, "Theme Chronicle Model: Chronicle Consists of Timestamp and TopicalWords over

- Each Theme," in Proceedings of the 21st ACM international conference on Information and knowledge management CIKM '12, New York, New York, USA: ACM Press, Oct. 2012, p. 2065, ISBN: 9781450311564. DOI: 10.1145/2396761.2398573. [Online]. Available: http://dl.acm.org/citation.cfm? id=2396761.2398573.
- [5] M. Jayashri and P. Chitra, "Topic clustering and topic evolution based on temporal parameters," in 2012 International Conference on Recent Trends in Information Technology, IEEE, Apr. 2012, pp. 559–564, ISBN: 978-1-4673-1601-9. DOI: 10.1109/ICRTIT. 2012.6206816. [Online]. Available: http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=6206816.
- [6] H. Park, E. Kim, K.-J. Bae, H. Hahn, T.-E. Sung, and H.-C. Kwon, "Detection and Analysis of Trend Topics for Global Scientific Literature Using Feature Selection Based on Gini-Index," in 2011 IEEE 23rd International Conference on Tools with Artificial Intelligence, IEEE, Nov. 2011, pp. 965–969, ISBN: 978-1-4577-2068-0. DOI: 10.1109/ICTAI.2011.166. [Online]. Available: http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=6103457.
- [7] H. Abe and S. Tsumoto, "Evaluating a method to detect temporal trends of phrases in research documents," in 2009 8th IEEE International Conference on Cognitive Informatics, IEEE, Jun. 2009, pp. 378–383, ISBN: 978-1-4244-4642-1. DOI: 10.1109/COGINF.2009.5250711. [Online]. Available: http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=5250711.
- [8] O. Cimenler, K. a. Reeves, and J. Skvoretz, "A regression analysis of researchers social network metrics on their citation performance in a college of engineering," *Journal of Informetrics*, vol. 8, no. 3, pp. 667–682, Jul. 2014, ISSN: 17511577. DOI: 10.1016/j.joi.2014.06.004. [Online]. Available: http://linkinghub.elsevier.com/retrieve/pii/S1751157714000571.
- [9] C. Trucolo and L. Digiampietri, "Uma revisão sistemática acerca das técnicas de identificação e análise de tendências," in X Simpósio Brasileiro de Sistemas de Informação (SBSI 2014), Londrina, 2014, pp. 639–650.
- [10] L. Digiampietri, J. Mena-Chalco, G. S. Silva, L. Oliveira, A. Malheiro, and D. Meira, "Dinâmica das relações de coautoria nos programas de pósgraduação em computação no brasil," in *Brazilian Workshop on Social Network Analysis and Mining (BraSNAM)*, 2012.
- [11] H. Nakagawa and T. Mori, "A simple but powerful automatic term extraction method," in COLING-02 on COMPUTERM 2002: Second International Workshop on Computational Terminology Volume 14, ser. COMPUTERM '02, Stroudsburg, PA, USA: Association for Computational Linguistics, 2002, pp. 1–7. DOI: 10.3115/1118771.1118778. [Online].

- Available: http://dx.doi.org/10.3115/1118771.1118778.
- [12] L. A. Digiampietri, J. P. Mena-Chalco, P. O. S. Vaz de Melo, A. P. R. Malheiro, D. N. O. Meira, L. F. Franco, and L. B. Oliveira, "Brax-ray: an x-ray of the brazilian computer science graduate programs," *PLoS ONE*, vol. 9, no. 4, e94541, Apr. 2014. DOI: 10.1371/journal.pone.0094541. [Online]. Available: http://dx.doi.org/10.1371%2Fjournal.pone.0094541.
- [13] A. Laender, C. de Lucena, J. Maldonado, E. de Souza e Silva, and N. Ziviani, "Assessing the research and education quality of the top Brazilian Computer Science graduate programs," ACM Special Interest Group on Computer Science Education, vol. 40, no. 2, pp. 135–145, 2008.



Caio Cesar Trucolo is a the bachelor in Information Systems at the University of São Paulo (2011). Nowadays he is a master student in Information Systems at the School of Arts, Sciences and Humanities at USP (EACH - USP). He has experience in the area of Computer Science, with emphasis in Information Systems, working mainly in the area of social network analysis and data mining.



Luciano Antonio Digiampietri (corresponding author) is a bachelor (2002) and a PhD (2007) in Computer Science at the Campinas State University (2002). Since April/2008 he has been a researcher professor in Information Systems at the School of Arts, Sciences and Humanities at USP (EACH - USP) and since 2010 he has been a professor at the graduate program in Information Systems at the University of São Paulo. He has experience in the area of Computer Science with empha-

sis in Computational Biology, Databases and Artificial Intelligence, working mainly on the following topics: scientific workflows, Bioinformatics, data provenance, automatic service composition, data mining and social network analysis.

E-mail: digiampietri@usp.br.